



Typ / Type: <b>ER/EQ 350-2</b>		Art.-No.: <b>E10-35010 / E00-35010</b>	
U	230V (50Hz)	$\Delta p_{fa}$ min	-- Pa
P <sub>1</sub>	0,98 kW	$\Delta I$	16 %
I <sub>N</sub>	4.3 A	I <sub>A</sub> / I <sub>N</sub>	2.7
n	2670 min <sup>-1</sup>		IP54
C <sub>400V</sub>	20 $\mu$ F		01.025
t <sub>R</sub>	40 °C		12 / 14 kg

Typ / Type: <b>DR/DQ 350-2</b>		Art.-No.: <b>E10-35060 / E00-35060</b>	
U	400V (50Hz)	$\Delta p_{fa}$ min	-- Pa
P <sub>1</sub>	0,86 kW	$\Delta I$	9 %
I <sub>N</sub>	1.62 A	I <sub>A</sub> / I <sub>N</sub>	4.4
n	2680 min <sup>-1</sup>		IP54
C <sub>400V</sub>	-- $\mu$ F		01.006
t <sub>R</sub>	55 °C		12 / 14 kg

**Geräusche / Sound levels:**

LWA <sub>rel</sub> A-bewertet bei V=0,5*V <sub>max</sub> LWA <sub>rel</sub> A-weighted at V=0,5*V <sub>max</sub>	f <sub>M</sub> [Hz]						
	125	250	500	1K	2K	4K	8K
LWA <sub>5</sub> [dB(A)] Gehäuse / casing	78	81	81	84	84	82	74

LWA <sub>rel</sub> A-bewertet bei V=0,5*V <sub>max</sub> LWA <sub>rel</sub> A-weighted at V=0,5*V <sub>max</sub>	f <sub>M</sub> [Hz]						
	125	250	500	1K	2K	4K	8K
LWA <sub>5</sub> [dB(A)] Gehäuse / casing	78	81	81	84	84	82	74

**Schaltbild / Wiring diagram:**

**Maße / Dimensions:**

(alle Maße in mm / all dimensions in mm)

